



Advantage Multifunction Camera System



Product Description

The Advantage MultiCAM multifunction videosystem incorporates light source, camera, USB (still image) or SD Card (WMV motion recording) archiving feature and TFT monitor in one attractive system. Camera control functions include: White balance, Window, Boost, Anti-Moiré. The camera features a high resolution SONY sensor. Image grabbing via Image capture software transferred to USB stick or SD card which can then be easily moved to a computer via a standard USB Port or card reader. The integrated silent running light source features high intensity 24 Watt metal halide lamp with a very small focal spot to produce maximum light output to the light guide. TFT-Monitor 10,4" with 800 x 600 dots resolution for a perfect image without the need of external monitor. This system is characterised by its compactness, easy handling, excellent value and attractive design.

Technical Data

Video System PAL PAL 440.000 pixel 752 (H) x 582 (V): Video Resolution 470 TV-lines
Shutter Range 1/50 sec - 1/100.000 sec, Sensitivity 0,9 Lux (f:1,4), Video Outputs 1 x BNC,
Lamp XENON metal halide short arc, lamp, 24 Watt, 5.500 °K colour temperature, Power Supply
90 VAC - 260 VAC, Dimensions (WxHxD) 294 x 95 x 250 mm, Weight CCU: 6 kg, Camera head:
65 g

Class 1, Manufactured and IEC 601-1 / tested acc. EN 60601-1, 93/42 ECC
(Please state which required), 10,4" TFT with 800 x 600 dots resolution, 50 - 60 Hz, Monitor,
Archiving system USB-Stick or SD card

Models

Advantage Multifunction USB
Advantage Multifunction Motion

AMUSB300ES
AMMOT300ES